



REDUCE LABOUR COSTS • INCREASE PRODUCTIVITY • WORK SAFER
Internationally patented • Manufactured by TORNOMECCANICA

WHAT MAKES SECUREPULLEY® DIFFERENT

- Designed with an automatic braking system that prevents a lifted or lowered load from falling should the operator lose control of the rope
- Allows the operator to rest or to pause during the lifting or lowering of (heavy) loads
- Only rope sheave for industry that conforms to the safety requirements of machinery directive ECC 89/392 and displays the **CE** mark

FEATURES

- Reduced risk to people and equipment from falling loads
- Simplicity and reliability
- Negative braking, i.e. as the human action ceases
- Constant effectiveness at different working heights
- Lowering of unloaded rope



Optional Slewing Arm

SPECIFICATIONS

- | | |
|--|----------------------------|
| • Pulley weight | 4.6kg |
| • Maximum load | 50kg |
| • Minimum load | 8 ÷ 10kg |
| • Maximum working height | 40m |
| • Approved rope | Polypropylene or SteelFlex |
| • Approved rope diameter | 18/20mm |
| • Connection to standard scaffolding pipes | 48mm |

S.A.K. Services are the sole agents for SECUREPULLEY® in Southern Africa

24 Middle Road, Morningside, Johannesburg

Tel: +27 (0)11 783 8270 • Fax: +27 (0)86 689 2505 • Mobile: +27 (0)82 855 8686

Email: admin@sakservices.co.za • Website: www.sakservices.co.za